CannonVoIP

Product Data Sheet
cannonvoip.com

VoIP-ATA-1 Analog Telephone Adapter

Keep the phone you have. Or the fax.

The VoIP-ATA-1 puts one analog device on your Cannon VoIP system: a phone you already own, a fax machine, or a courtesy phone in the lobby. Plug the device into the adapter's phone jack, plug the adapter into your network, and it shows up as an extension on your account. Cannon VoIP sets it up remotely, so there is nothing to configure, and it is small enough to tuck behind the phone or mount on the wall.



Highlights

- Connects any standard analog phone, cordless base or fax machine
- Fax support: Cannon VoIP switches it into fax mode for you
- Caller ID, call waiting, hold, transfer, forwarding and 3-way calling
- Voicemail waiting indicator on phones that support it
- One phone jack (RJ11) and one network jack (RJ45)
- Powered by the included adapter or any USB port
- Status lights for power, network, registration and calls
- Hotline mode: dials a set number when the handset is lifted
- Desk or wall mount, about the size of a deck of cards
- Arrives configured for your account: plug it in and it registers

Analog Phone
Standard RJ11 jack

Fax Ready
Fax mode for fax machines

HD Voice
Wideband codecs

Caller ID
Name and number

3-Way
Conference calls

Ethernet
10/100 Mbps port

USB Power
Or the included adapter

Status Lights
Power, network, call

Compact
3.3 x 2.7 x 0.9 in

Zero Touch
Set up by Cannon VoIP

In the box

VoIP-ATA-1 adapter, power adapter, Ethernet cable, quick installation guide.

Backed by Cannon VoIP

Sold and supported by Cannon VoIP, headquartered in Fort Worth, TX. One team for your phones and internet. Questions? Call 888-973-0515.

VoIP-ATA-1 Specifications

CannonVoIP

General

- HD voice
- 1 analog phone port (FXS, RJ11)
- 1 network port (10/100 Mbps)
- Works with phones, cordless bases and fax machines
- Powered by the included adapter or a USB port
- Desk or wall mount
- Set up remotely by Cannon VoIP

Phone Features

- Caller ID (name and number) on your analog phone
- Voicemail waiting indicator
- Blocked and allowed caller lists
- Hotline: auto-dials a set number when the handset is lifted
- Fax mode for fax machines, set by Cannon VoIP
- US dial tone and ring patterns

Call Features

- Make, answer and reject calls
- Hold and resume
- Call waiting
- Caller ID
- Call forward (always, busy, no answer)
- Call transfer (attended and blind)
- Do Not Disturb
- Voicemail
- 3-way calling

Audio

- HD voice (wideband) support
- Echo cancellation
- Noise reduction
- Automatic gain control
- Packet loss concealment
- Adaptive jitter buffer for smooth calls on busy networks

Network

- 10/100 Mbps Ethernet port (RJ45)
- Powered by the included adapter or a USB port (no PoE)

Connections

- 1 x RJ11 phone port (FXS)
- 1 x RJ45 network port
- 1 x micro USB (power only)
- 1 x DC power (5V/1A)
- Reset button
- 4 status lights (power, network, registration, call)

In the Box

- VoIP-ATA-1 adapter
- Power adapter (5V/1A)
- Ethernet cable (1.5 m, CAT5e)
- Quick installation guide

Physical Specifications

- Phone port: 1 x RJ11 (FXS)
- Network port: 1 x RJ45, 10/100 Mbps
- Power: included 5V/1A adapter or micro USB
- Power use: 0.8 to 5.7 W
- Status lights: 4 (power, network, registration, call)
- Color: black
- Mounting: desktop or wall
- Operating temperature: 32 to 113°F (0 to 45°C)
- Operating humidity: 10 to 95%

Dimensions (L x W x H)

- 3.3 x 2.7 x 0.9 in (85 x 68 x 23 mm)

Need Help?

- Call 888-973-0515
- Local: 817-973-1570
- info@cannonvoip.com
- cannonvoip.com

Specifications are subject to change without notice.