CannonVoIP

Product Data Sheet
cannonvoip.com

VoIP-FXO-4 Analog Line Gateway

Bring your existing phone lines into Cannon VoIP.

The VoIP-FXO-4 connects up to four traditional phone lines to your Cannon VoIP system. Calls that come in on those lines ring your Cannon VoIP phones and apps like any other call, and your phones can call out over them too. Use it to keep a line you can't port yet, to keep a landline at a site that needs one, or to bridge a line during a move. Four line ports, two Ethernet ports and hardware echo cancellation in a compact case.



Highlights

- 4 line ports (FXO) for traditional phone lines from your carrier
- Calls on those lines ring your Cannon VoIP phones and apps
- 4 calls at once, one per line
- Caller ID on incoming calls
- Hardware echo cancellation for clear audio on analog lines
- Line disconnect alarm: a light comes on when a line goes dead
- Two Ethernet ports (10/100 Mbps)
- Incoming call block list and outgoing call limits per line
- Surge protection on the line ports
- Compact: 5.5 x 3.9 x 1.2 inches, desk or shelf

4 Lines
FXO ports (RJ11)

4 Calls
At once

Caller ID
On incoming calls

Echo Cancel
Hardware based

Line Alarm
Disconnect warning

2 Ethernet
10/100 Mbps ports

Block List
Incoming numbers

Surge Protected
Level 4, line ports

Compact
5.5 x 3.9 x 1.2 in

12V Power
Adapter included

In the box

VoIP-FXO-4 gateway, power adapter, Ethernet cable, quick installation guide.

Backed by Cannon VoIP

Sold and supported by Cannon VoIP, headquartered in Fort Worth, TX. One team for your phones and internet. Questions? Call 888-973-0515.

VoIP-FXO-4 Specifications

General

- 4 analog line ports (FXO, RJ11)
- 4 simultaneous calls
- 2 Ethernet ports (10/100 Mbps)
- Connects traditional phone lines to Cannon VoIP
- Hardware echo cancellation
- Desk or shelf mount

Line Features

- Caller ID detection
- Busy tone and disconnect detection
- Polarity reversal detection
- Line disconnect alarm
- Incoming call block list
- Outgoing calls can be barred per line
- Second-stage dialing

Call Features

- Calls in on a line ring your Cannon VoIP phones and apps
- Calls out over a line from your Cannon VoIP phones
- Caller ID passed through to your phones

Audio

- Hardware echo cancellation
- Touch-tone (DTMF) support for menus and extensions

Network

- 2 x 10/100 Mbps Ethernet ports

Connections

- 4 x RJ11 line ports (FXO)
- 2 x RJ45 Ethernet ports
- 1 x console port (mini USB)
- 1 x DC power (12V)
- Reset button (hold 8 seconds)
- Grounding stud
- Status lights: run, alarm, Ethernet 1, Ethernet 2, and one per line

In the Box

- VoIP-FXO-4 gateway
- Power adapter (12V)
- Ethernet cable
- Quick installation guide

Physical Specifications

- Line ports: 4 x RJ11 (FXO)
- Ethernet ports: 2 x RJ45, 10/100 Mbps
- Power: included 12V adapter
- Power use: under 2 W
- Surge protection: level 4 on the line ports
- Status lights: run, alarm, Ethernet 1 and 2, one per line
- Color: black
- Weight: 7 oz (0.2 kg)
- Operating temperature: 32 to 113°F (0 to 45°C)
- Operating humidity: 8 to 90%, non-condensing

Dimensions (W x D x H)

- 5.5 x 3.9 x 1.2 in (140 x 100 x 30 mm)

Need Help?

- Call 888-973-0515
- Local: 817-973-1570
- info@cannonvoip.com
- cannonvoip.com

Specifications are subject to change without notice.